

FIREBOX T15

Available with optional integrated wireless module Up to 90 Mbps UTM throughput, 3 x 1Gb ports



DATASHEET

ENTERPRISE-GRADE SECURITY FOR THE SMALL AND HOME OFFICES

Designed to protect enterprise users where they connect – in the small office/home office – Firebox® T15 allows businesses to extend powerful network security to the remote workforce. With more features than any other small form-factor UTM firewall in its market, Firebox T15 is a cost-effective security powerhouse that delivers enterprise-grade security in a small package.

By standardizing on WatchGuard for network security, we were able to decrease the average installation time bymore than 75 percent - now averaging anywhere from 15-20 [minutes] per site. We just plug the appliance in, itestablishes a connection and pulls the configuration file. We are then up and running, and free to focus our time on testing credit card processing and access to approved web sites.

~ Dustin McCreight, Product Manager, Network and Security Services, NCR Corporation

TOTAL NETWORK PROTECTION

Small businesses and remote locations have long been thought of as soft targets for attackers. WatchGuard Firebox T15 tabletop appliances bring enterprise-level network security to those small office/branch office and small retail environments that matches the reality of today's distributed work style. Our unique product architecture enables smaller businesses to leverage best-in-class security services – from URL filtering and intrusion prevention to application control and data loss prevention – minus the cost and complexity of managing multiple single-point solutions.

QUICK AND SIMPLE DEPLOYMENT

Cloud-based RapidDeploy technology, a configuration and deployment tool that comes standard with WatchGuard Firebox appliances, enables IT staff to create and store configuration data in the cloud and have a new appliance directly shipped to its destination. Once the device arrives, it can connect to the cloud for a secure download of its configuration settings, saving staff travel time and money. This technology is particularly advantageous for large distributed enterprises where managing a multitude of devices efficiently across multiple locations and geographies is critical.

EASY TO MANAGE AND UNDERSTAND

Firebox T Series appliances are not only easy to initially configure and deploy, they are also designed with an emphasis on centralized management, making ongoing policy and network management simple and straightforward. WatchGuard Dimension provides a suite of big data visibility and reporting tools that instantly identify and distill key network security threats, issues and trends so you can take immediate preventive or corrective action. Security is complex, running it doesn't have to be.

PROTECT WHERE YOU CONNECT

Distributed workstyles require organizations to rethink how they secure their employees while in home, shared suite, and co-office environments. Firebox T15 brings full UTM protection to the remote worker without requiring back-hauling traffic through the corporate network.

FEATURES & BENEFITS

- Wireless versions of the T15 use 802.11b/g/n operating in the 2.4 GHz and 5GHz bands for high performance and superior reliability.
- All logging and reporting functions are included with purchase, with over 100 dashboards and reports including PCI and HIPAA.
- 3 Gigabit Ethernet ports support high-speed LAN backbone infrastructures & gigabit WAN connections.
- Nothing could be easier than WatchGuard's drag-and-drop Branch Office VPN setup – three clicks and your remote office is connected.

Firebox T Series	T15/T15-W		
THROUGHPUT			
Firewall	400 Mbps		
Firewall (IMIX)	120 Mbps		
VPN (UDP 1518)	150 Mbps		
VPN (IMIX)	46 Mbps		
Antivirus	120 Mbps		
IPS (fast/full scan)	160 Mbps / 80 Mbps		
UTM (fast/ full scan)	90 Mbps / 52 Mbps		
CAPACITY			
Interfaces 10/100/1000*	3		
PoE ports	N/A		
I/O interfaces	1 SRL/1 USB 2.0		
Concurrent connections	100,000		
Concurrent connections (proxy)	95,000		
New connections per second	2,400		
VLANs	10		
WSM licenses (incl)	0		
TDR Host Sensors included	5		
Authenticated users limit	200		
VPN TUNNELS			
Branch Office VPN	5		
Mobile VPN	5		
SECURITY FEATURES			
Firewall	Stateful packet inspection, deep packet inspection, proxy firewall		
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3, POP3S, SMTP, IMAP, IMAPS, and Explicit Proxy		
Threat protection	DoS attacks, fragmented & malformed packets, blended threats & more		
VoIP	H.323, SIP, call setup and session security		
Filtering options	Browser Safe Search, Google for Business		
VPN & AUTHENTICATION			
Cloud providers	AWS (Static/Dynamic), Azure (Static/Dynamic)		
Encryption	AES 256-128 bit, 3DES, DES		
IPSec	SHA-2, IKEv1/v2, IKE pre-shared key, 3rd party cert, Suite B		
Single sign-on	Windows, Mac OS X, mobile operating systems, RADIUS		
Authentication	RADIUS, LDAP, Windows Active Directory, VASCO, RSA SecurID, internal database, Duo, SMS Passcode		
MANAGEMENT			
Logging and notifications	WatchGuard, Syslog, SNMP v2/v3		
User interfaces	Centralized console (WSM), Web UI, scriptable CLI		
Reporting	WatchGuard Dimension includes over 100 pre-defined reports, executive summary and visibility tools		
CERTIFICATIONS			
Security	Pending: CC EAL4+, FIPS 140-2		
Safety	NRTL/C, CB		
Network	IPv6 Ready Gold (routing)		
Hazardous substance control	WEEE, ROHS, REACH		
NETWORKING			
Routing	Static, SD-WAN Dynamic Path Selection		
P address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS		
NAT	Static, dynamic, 1:1, IPSec traversal, policy-based		
	Optional integrated 802 11b/g/p dual band 24 GHz and 5 GHz		



PHYSICAL AND POWER SPECIFICATIONS

Product Dimensions	7.5" x 6.0" x 1.25" (19 x 15.2 x 3.2 cm)		
Shipping Dimensions	12.5" x 7.25" x 2" (32 x 18.4 x 5 cm)		
Shipping Weight	3.1 lbs (1.4 Kg)		
AC Power	100-240 VAC Autosensing		
Power Consumption	U.S. 15 Watts (51 BTU/hr) (max)		
ENVIRONMENT	OPERATING	STORAGE	
Temperature	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C	
Relative Humidity	10% to 85% non-condensing	10% to85% non-condensing	
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)	
MTBF	129,955 hours at 104° F(40° C)		

STRONG SECURITY AT EVERY LAYER

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing and much more. Total and Basic Security Suite packages are available on all Firebox solutions.

Features & Services	TOTAL SECURITY SUITE	Basic Security Suite
Intrusion Prevention Service (IPS)	\checkmark	\checkmark
App Control	\checkmark	\checkmark
WebBlocker	\checkmark	\checkmark
spamBlocker	\checkmark	\checkmark
Gateway AntiVirus	\checkmark	\checkmark
Reputation Enabled Defense (RED)	\checkmark	√
Network Discovery	\checkmark	√
APT Blocker	\checkmark	
Data Loss Protection (DLP)	\checkmark	
Threat Detection & Response	\checkmark	
DNSWatch	\checkmark	
Access Portal*	✓	
IntelligentAV*	✓	
Dimension Command	✓	
Support	Gold (24x7)	Standard (24x7)

For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. You can also refer to the Appliance Sizing Guide at www.watchguard.com/sizing.

U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895

Wi-Fi module

Wireless

Optional integrated 802.11b/g/n dual band 2.4 GHz and 5 GHz

WEB www.watchguard.com

No express or implied warranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. © 2018 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard, free and logo, Firebox, and Fireware are registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE67042_103118